

FREE PROJECT SHEET AIRSTREAM QUILT | SIZE 241/2" x 38"



DESIGN MICHELLE ENGEL BENCSKO

TECHNICAL EDITOR LINDA SPIRIDON

MATERIALS

AIRSTREAM QUILT FEATURING CIRRUS SOLIDS BY CLOUD9 FABRICS

Note: This quilt is made using the 60 degree triangle ruler from Creative Grids (necessary for accurate measurement and cutting)

1/3 yard of each: Glow, Blush, Mist

1 yard Limestone for Background

¹/₃ yard Limestone for Binding

11/3 yards Ash for Backing

Note: All possible care has been taken to assure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

CUTTING DIRECTIONS

Cutting dimensions include 1/4" seam allowances.

From Limestone:

18-6½" x 3¾" rectangles subcut into:

- 9- rectangles on the diagonal as in [fig 1]
- 9- rectangles on the diagonal as in [fig 2]
- 4- 3½" x WOF strips (sashing)

From Glow:

- 2- 3½" x WOF strip subcut into:
 - 1- 3½" x 30" strip
 - 1- 3½" x 15" strip
 - 1- 2¾" x 15" strip
- 1-2¾" x WOF strip subcut into:
 - 1- 2¾" x 30" strip

From Blush:

- 2- 3½" x WOF strip subcut into:
 - 1- 3½" x 30" strip
 - 1- 3½" x 22" strip
- 1-2¾" x WOF strip subcut into:
 - 1- 2¾" x 22" strip
 - 1- 2¾" x 15" strip

From Mist:

- 1- 3½" x WOF strip subcut into:
 - 1- 3½" x 22" strip
 - 1- 3½" x 15" strip
- 2-2¾" x WOF strip subcut into:
 - 1- 2¾" x 30" strip
 - 1- 2¾" x 22" strip

ASSEMBLY DIRECTIONS

BLOCK ASSEMBLY: TWO-FABRIC TRIANGLES

1. Using ¼" seam allowance, sew strips together noting fabric color and strip measurements as stated:

STRIP SET	Top strips are 3½" TOP		Bottom strips are 23/4" BOTTOM	CUT TRIANGLES
Sew 30" strips	Blush	to	Glow	4
Sew 15" strips	Glow	to	Blush	2
Sew 22" strips	Mist	to	Blush	3
Sew 22" strips	Blush	to	Mist	3
Sew 30" strips	Glow	to	Mist	4
Sew 15" strips	Mist	to	Glow	2

- 2. Cut the number of triangles stated in step 1 for each pieced strip using the 60 degree ruler, aligning the 3¼" mark on the ruler at the seam line and the bottom edge of the strip set on the 5¾" ruler line. Cut triangles next to each other. *Do not* flip ruler. [fig 3]
- 3. Refer to the QUILT DIAGRAM for pieced triangle colors. Pin the left and right side limestone triangles to each main triangle. Note the triangles vary direction with each block. [fig 4]

- 4. Sew the side triangles to each main triangle. Lay the left side triangle (RST) on top of pieced triangle extended over top edge, sew ¼" seam allowance. Press. Repeat with right side triangle. [fig 5]
- 5. Square up each block to $6\frac{1}{2}$ " w x $5\frac{3}{4}$ " h. Use top of triangle as a center point and leave $\frac{1}{4}$ " seam allowance at triangle top point. [fig 6]

ASSEMBLING THE QUILT

- 6. Referring to the QUILT DIAGRAM for color placement, arrange the blocks in six horizontal rows of three blocks each. Sew the blocks together in rows, pressing seam allowances going in one direction alternating directions from row to row. Sew the rows together to complete quilt top.
- 7. Measure length of quilt top (approximately 32") and cut (2) 3½" limestone sashing strips to equal that length. Sew a strip to each side of the quilt top.
- 8. Repeat Step 7 measuring the width of quilt top (approximately 24½"). Sew the strips to the top and bottom to complete quilt top.
- 9. Layer the quilt top, batting, and backing. Baste, quilt, and bind.



